



legacy
luxury veneered flooring

Technical sheet

0.6mm on 8mm HDF with 2MM cork backing – 1200 x 240 x 8,6mm



Zabok XL
0104012304

Sisak XL
0104012204

Lovinac XL
0104012104

Bistra XL
0104012404

OVERALL SIZE

1200 x 240 x 8,6
mm

15
YEARS
RESIDENTIAL WARRANTY

5
YEARS
COMMERCIAL WARRANTY

BOARD STRUCTURE

FINISH

Lacquered (UV varnish)

Top layer

0.6 mm European oak (nominal) rustic light

Middle layer


7 mm high density fibreboard (HDF)
Swelling max. 15% in 24 hours

Backing

1 mm cork

Locking

Uniclic



Average density of the board is 870 kg per m³, on the surface up to 1200 kg per m³.

The bonding agent between the top layer (veneer) and the supporting middle layer (HDF) is a D3 waterproof glue (PVAc) especially developed for pressing and veneering.

Lacquering system

The lacquering process is designed to achieve great results regarding water protection and abrasion resistance. All edges are sealed with a water resistant sealer on the V-groove.

Underfloor heating

Floor can be used on underfloor heating with a maximum temperature of 27 degrees Celsius

FLEXURA
WOODEN FLOORS

flexura-floors.be

FLEXURA
WOODEN FLOORS

FLEXIBLE IN EVERY SENSE