

**General specifications**

Type of floor	Varnished veneer floor
SKU#	<i>(Per product type)</i>
Wood specie	Oak
Grading	Select / Rustic Light
Pattern	Herringbone
Finish	Elastic varnish program
Staining	Water based colors
Thickness of the top layer	0.6 mm
Core	HDF Q10
Click system	Uniclic® A+B

**Technical information**

Flexura Floors NV , Schoendalestraat 306, B-8792 Desselgem, Belgium, production site. Issued in accordance with the construction products directives (CPD) nr. VP003.

Declares that the *Herringbone Collection* conform to type as required by the Council Directives 89/106/EEC of 21st December 1988 on construction products and also evidenced by the conformity under attestation system 3 of Appendix Z.A2 of EN14342:2013.

Swelling rate of the HDF board	≤ 10% in 24 h
Density of the HDF board	870 kg/m <sup>3</sup>
Formaldehyde emission EN12460-3	E1
Content of PCP	<5 ppm
Falling sand	5400 cycles
Scratch test (1 is best – 5 is worst)	1
Gloss level	Matt between 3-5
Cross hatch adhesion (cross cut test) (0 is best – 5 is worst)	1

**Size and packaging information**

Length	730 mm
Width	146 mm
Height	9 mm
Quantity per carton	9 pcs
M <sup>2</sup> per carton	0.96 sqm
Weight per carton	7.5 KG
M <sup>2</sup> per full pallet	96 m <sup>2</sup>
Weight per full pallet	785 KG

**Certificates**

CE	EN 14342:2013 Veneered floor covering with surface coating
FSC	On request FSC® MIX C159816